## *ESUNCOLOR*

# 

#### Leveraging Light and Innovation for a Sustainable Future

- HTLT<sup>™</sup> Additives are a mixture of transparent, high temperature resistant, organic/inorganic, sustainable materials.
- HTLT<sup>™</sup> Additives deliver a comprehensive menu of totally integrated features & benefits for thermoplastic processing and performance.
- HTLT<sup>™</sup> Additives offer design versatility allowing for the transformation of existing thermoplastic resins into a new product line of higher performing transparent composite thermoplastics.
- HTLT<sup>™</sup> Additives are employed in conventional processing equipment as a masterbatch, or as either coated pellets or as a free flowing, homogeneous, dry powder for conventional compounding.



HTLT<sup>™</sup> Multi-Functional Diagram

Opportunity for Suncolor's High Temperature Thermoplastic Additives (HTLT<sup>™</sup>) is driven by robust, growing demand for high heat polymers, with stringent performance requirements for evolving applications in major industries. Current trends, such as miniaturization, weight reduction, improved optics and connectivity, with tight tolerances, mass production capability and ease of processability require new high-performance thermoplastics. HTLT<sup>™</sup> Additives transform existing high performance thermoplastic resins into new higher performance products with balanced, totally integrated performance properties.

HTLT<sup>™</sup> Masterbatch Additives and HTLT<sup>™</sup> Powder Additives are available for polycarbonate, polyetherimide, polyimide, polyphenylsulfone, and certain co-polymer compositions. These HTLT<sup>™</sup> Additive modified thermoplastics are characterized by high transparency, broad glass transition temperatures ranging from 220°C to 300°C, CTE's as low as 18 ppm, very low mold-in stress, and sub-micron replication of detail. Both neat and glass or fiber reinforced thermoplastic performance and processing benefit from the addition of HTLT<sup>™</sup> Additives. Glass and fiber reinforcement fillers have a substantially lower CTE than a host polymer in a composite formula. The HTLT<sup>™</sup> Additives lower the CTE of the host polymer, making the thermal expansion of the host polymer more compatible with the thermal expansion of the reinforcing filler over a range of temperatures.

#### Total Integrated Thermoplastic Performance Properties, Features & Benefits Achieved by HTLT™ Additives:

- High Transparency, Visible & Near Infrared Light
- High Glass Transition Temperature (Tg) (220°C-300°C)
- Coefficient of Thermal Expansion (CTE) (18-50 ppm)
- Low Birefringence, High Index of Refraction (> 1.6)
- Low Mold-In Stress; Uniform Heating & Cooling
- Increased Thermal Conductivity
- High Heat Processes such as SMT Reflow
- Geometric Stability during & after Processing
- True Replication of Sub-Micron Detail

- Injection Moldable
- Reduced Cycle Times (Up to 40%)
- Homogeneity/ Compatibilization
- Impact Resistance & Chemical Resistance
- High Operating Temperatures (≥150° C)
- Surface Treatable / AR and High Temperature Coatings
- High Thermal Stability (400-450°C/ TGA)
- Thermal, Photolytic & Hydrolytic Oxidative Resistance
- Inherent, Non-Halogenated Fire Retardancy

HTLT <sup>™</sup> Additive	Base Resin	Neat Additive	Additive MasterBatch
HTLT™ TPI	Thermoplastic Polyimide	Free-Flowing Dry Powder	Pellets or Powder
HTLT™ PEI	Polyetherimide	Free-Flowing Dry Powder	Pellets or Powder
HTLT™ PPSU	Polyphenylsulfone	Free-Flowing Dry Powder	Pellets or Powder
HTLT™ TPI/PPSU	Polyimide/Polyphenylsulfone	Free-Flowing Dry Powder	Pellets or Powder
HTLT™ PC/XT	Polycarbonate	Free-Flowing Dry Powder	Pellets or Powder

### *ESUNCOLOR*

#### **TECHNICAL DATA SHEET:**

THE INFORMATION IN THE PRODUCT AND TECHNICAL DATA SHEETS ATTACHED HERETO IS SUNCOLOR CORPORATION INFORMATION. SUNCOLOR PRODUCTS DISCUSSED HEREIN ARE DEVELOPMENTAL. THE PRODUCT SHEETS AND THE INFORMATION CONTAINED IN THE DATA SHEETS DO NOT CONSTITUTE AN OFFER FOR SALE. VALUES AND OTHER PERFORMANCE PROPERTIES LISTED ARE REASONABLY EXPECTED USING THE PROCESSING METHODS RECOMMENDED. PROCESSING CONDITIONS CAN CAUSE MATERIAL PROPERTIES TO SHIFT FROM THE VALUES STATED IN THE INFORMATION. THIS DOCUMENT IS THE PROPERTY OF SUNCOLOR CORPORATION AND THIS DOCUMENT, IN WHOLE OR PART, IS NOT TO BE COPIED, USED, OR DISTRIBUTED, OR OTHERWISE DISCLOSED WITHOUT THE PRIOR WRITTEN CONSENT OF SUNCOLOR CORPORATION. A LIST OF SUNCOLOR CORPORATION HTLT™ TECHNOLOGY RELATED PATENTS IS AVAILABLE FROM SUNCOLOR CORPORATION UPON REQUEST.

THE NAME OR MARK HTLT™ IS A TRADEMARK OF SUNCOLOR CORPORATION.